

CBV 0.6/1.0KV 1.5mm<sup>2</sup> SHANGHAI HANKE DIANXIAN YOUXIAN GONGSI

#### 应用范围

适用于额定电压600/1000V及以下船用电线电缆。

#### APPLICATIONS

Marine wires and cables with rated voltage of not more than 600/1000V.

#### 电线结构

多股绞合镀锡铜丝导体；  
PVC绝缘。

#### WIRE MAKE-UP

Multi-stranded tincopper conductor;  
PVC insulation

#### 技术参数

- 温度范围：-10℃ ~ +80℃
- 额定电压：U<sub>0</sub>/U 600/1000V
- 符合标准：企标
- 导体标准：GB/T 3956-1997 第2种

#### TECHNICAL DATA

- Operating Temp.: -10℃ ~ +80℃
- Rated Voltage: U<sub>0</sub>/U 600/1000V
- Governing Standards: Enterprise standard
- Conductor Standards: Category 2 in GB/T 3956-1997

导体截面 Cross Section mm <sup>2</sup>	导体结构 Conductor Structure 根数/单根直径 Cond. No./O.D	标称外径 Nominal O.D. mm	最大外径 Max O.D. mm	重量(近似) Approx. Weight Kg/Km
0.5	7/0.30	3.10	3.6	15.8
0.75	7/0.37	3.31	3.9	19.3
1	7/0.43	3.69	4.5	15.6
1.5	7/0.52	3.96	4.8	31.2
2.5	7/0.68	4.44	5.4	44.0
4	7/0.85	4.95	6.0	61.0
6	7/1.04	5.52	6.6	83.7
10	7/0.35	6.45	7.6	129
16	7/1.70	7.70	9.0	197
25	7/2.14	9.22	11.0	300
35	19/1.53	10.85	12.5	411
50	19/1.78	12.30	14.0	546
70	19/2.14	14.50	16.5	778
95	19/2.52	16.60	19.0	1060