

UTP CAT.5E 4×2×24AWG SHANGHAI HANKE WIRE CO., LTD.

UTP CAT.6 4×2×24AWG SHANGHAI HANKE WIRE CO., LTD.

应用范围

适用于楼宇和办公场所高密度终端和局域网络的布线。

APPLICATIONS

Suitable for LAN cabling in office buildings with densely-distributed terminals.

电线结构

单根裸铜丝导体，四线对整体绞合，各类形式屏蔽；PE绝缘，PVC护套。

WIRE MAKE-UP

Single bare copper conductor; four twisted-pair generally stranded, various shield; PE insulation, PVC sheath

技术参数

- 温度范围：-10℃ ~ +70℃
- 符合标准：EIA/TIA-568、YD/T 1019、ISO/IEC 11801
- 导体标准：UL 24AWG

TECHNICAL DATA

- Operating Temp.: -10℃ ~ +70℃
- Governing Std.: EIA/TIA-568, YD/T 1019, ISO/IEC 11801
- Conductor Std.: UL 24AWG

导体截面 Cross Section 对数 × 芯数 × mm ² Pair No. × Core No. × mm ²	导体结构 Conductor Structure 对数 × 根数/单根直径 Pair No. × Cond. No./O.D	标称外径 Nominal O.D. mm	最大外径 Max O.D. mm	重量(近似) Approx. Weight Kg/Km
UTP (CAT.5e 无屏蔽型)				
4×2×0.2	4×2×1/0.51	4.40	4.9	30.0
FTP (CAT.5e 绕包总屏蔽型)				
4×2×0.2	4×2×1/0.51	5.30	5.8	50.0
STP (CAT.5e 绕包+编织屏蔽型)				
4×2×0.2	4×2×1/0.51	5.10	5.6	40.0
UTP (CAT.6 无屏蔽型)				
4×2×0.2	4×2×1/0.51	4.70	5.2	40.0
FTP (CAT.6 绕包总屏蔽型)				
4×2×0.2	4×2×1/0.51	5.30	5.8	50.0