

国外标准电线电缆系列 FOREIGN STANDARDS-BASED WIRES & CABLES

UL CUL 认可号:
E255620



表面印字: E255620 AAWM2464 80℃ 300V VW-1 × ×AWG SHHKW AWM I A 80℃ 300V FT-1

应用范围

适用于广播、视听、仪器、电脑等设备的连接线。

APPLICATIONS

For wiring of broadcaster, audio-visual units, instruments, computers.

电线结构

多股细束绞裸铜丝或镀锡铜丝导体, PVC绝缘、护套;

WIRE MAKE-UP

Multi-stranded fine bare copper/tincopper conductor
PVC insulation, PVC sheath

技术参数

- 温度范围: 80℃
- 额定电压: 300V
- 符合标准: UL 758, 1581

TECHNICAL DATA

- Operating Temp.: 80℃
- Rated Voltage: 300V
- Governing Std.: UL 758, 1581

规格 Size 芯数 × AWG Core No × AWG	导体结构 Conductor Structure 芯数 × 根数/单根直径 Core No. × Cond. No./O.D	标称外径 Nominal O.D. mm	最大外径 Max.O.D. mm	重量(近似) Approx. Weight Kg/Km
2 × 28	2 × 7/0.127	3.32	3.6	14.0
2 × 26	2 × 7/0.16	3.52	3.8	16.0
2 × 24	2 × 11/0.16	3.82	4.1	19.2
2 × 22	2 × 17/0.16	4.15	4.5	23.1
2 × 20	2 × 26/0.16	4.62	4.9	30.0
2 × 18	2 × 41/0.16	5.68	6.0	39.6
3 × 28	3 × 7/0.127	3.46	3.8	16.3
3 × 26	3 × 7/0.16	3.67	4.0	19.0
3 × 24	3 × 11/0.16	4.00	4.3	23.3
3 × 22	3 × 17/0.16	4.32	4.6	28.6
3 × 20	3 × 26/0.16	4.86	5.2	38.2
3 × 18	3 × 41/0.16	6.00	6.3	51.4