


CE 认可号:
CE100103002607

CE H03VV-F 300/300V 4 × 0.75mm² SHANGHAI HANKE WIRE CO., LTD.



H03VVH2-F 300/300V 2 × 0.75mm² SHANGHAI HANKE WIRE CO., LTD.



应用范围

适用于安装电器装置、仪器仪表、电信设备、动力和照明等内部各部件的固定连接。

APPLICATIONS

Suitable for fixed wiring of electric appliances, instruments/gauges, telecommunication equipment, power and lighting.

电线结构

多股细裸束绞铜丝或镀锡铜丝导体;
PVC绝缘、护套。

WIRE MAKE-UP

Multi-stranded fine bare copper/tincopper conductor
PVC insulation and sheath

技术参数

- ① 温度范围: -30°C ~ +70°C
- ② 额定电压: U₀/U 300/300V(H03VV-F、H03VVH2-F)
300/500V(H05VVH2-F)
- ③ 符合标准: VDE 0281
- ④ 导体标准: VDE 0295/IEC 60228 5类

TECHNICAL DATA

- ① Operating Temp.: -30°C ~ +90°C
- ② Rated Voltage: U₀/U 300/300V(H03VV-F、H03VVH2-F)
300/500V(H05VVH2-F)
- ③ Governing Std.: VDE 0281
- ④ Conductor Std.: Category 5 in VDE 0295/IEC 60228

导体截面 Corss section 芯数 × mm ² Core No. × mm ²	导体结构 Conductor Structure 芯数 × 根数/单根直径 Core No. × Cond. No./O.D	标称外径 Nominal O.D. mm	最大外径 Max.O.D. mm	重量(近似) Approx. Weight Kg/Km
(H03VV-F) 300/300V				
2 × 0.5	2 × 16/0.20	5.13	5.9	39.0
2 × 0.75	2 × 24/0.20	5.65	6.3	48.0
3 × 0.5	3 × 16/0.20	5.43	6.3	46.0
3 × 0.75	3 × 24/0.20	5.99	6.7	58.0
4 × 0.5	4 × 16/0.20	5.94	6.9	55.0
4 × 0.75	4 × 24/0.20	6.57	7.3	71.0

导体截面 Corss section 芯数 × mm ² Core No. × mm ²	导体结构 Conductor Structure 芯数 × 根数/单根直径 Core No. × Cond. No./O.D	标称外径 Nominal O.D. mm	最大外径 Max.O.D. mm	重量(近似) Approx. Weight Kg/Km
※ (H03VV2H-F) 300/300V				
2 × 0.5	2 × 16/0.20	3.17 × 5.13	3.7 × 5.9	26.6
2 × 0.75	2 × 24/0.20	3.43 × 5.65	3.8 × 6.3	34.5
※ (H05VV2H-F) 300/500V				
2 × 0.75	2 × 24/0.20	4.03 × 6.46	4.5 × 7.2	42.3
2 × 1	2 × 32/0.20	4.17 × 6.74	4.7 × 7.5	55.1

※ 未CE、VDE认证